



WELD SHEAR U-C 4+S

BATTERY DRIVE FOR MAXIMUM FLEXIBILITY

The U-C 4 +S® weld shear combines the robustness and power of the conventional shearing devices in the U-L series with the advantages of an integrated battery drive. This means that less equipment is required on the construction site. The shearing can be carried out safely, quickly and reliably at the touch of a button.

POWERED BY
EGO™

TECHNICAL DATA

SPECIFICATIONS

Dimensions (L x W x H)	847 x 455 x 322 mm
Weight	45 kg (without battery, without shear blades)
Motor	Battery drive
Power	1.5 kW
Battery	12 Ah / 56 V, 1 piece
Pressure	200 kN
Rail type	Flat-bottom rail
Gap width	Up to 75 mm / 90 mm (Thermit® Head Repair, 150 mm stroke)

BENEFITS

- 2-in-1 weld shear – less equipment required on the construction site
- Independent of external hydraulic units
- Up to 40 shearing operations per battery charge
- Commercially available lithium-ion battery
- Charging time of just 75 minutes for a 12 Ah battery
- Multiple charging options available, including mobile charging

CONTENTS

- Weld shear U-C 4 +S®

ACCESSORIES

- Shear blades, profile-adapted
- 12 Ah lithium-ion battery
- Charging options tailored to your needs

