



GOLDSCHMIDT

Smart Rail Solutions



RAIL SAW SR 310 H

CUTTING YOUR RAILS WITH EASE

Our Rail Saw SR 310 H with its bell-crank clamp offers improved ergonomics and optimum protection as well as precise cutting results. Additionally, the working time is reduced significantly due to its reversible feature allowing the user to cut from either side of the rail. Hydraulic driven for maximum power compared to combustion driven tools.

TECHNICAL DATA

SPECIFICATIONS

Motor	Hydraulic
Hydraulic system	Open center
Weight rail saw	17 kg / 39 lbs
Weight Cell crank clamp	11 kg / 24 lbs
Dimensions	1 143 x 686 x 457 mm 45 x 27 x 18 inch
Max. pressure	140 bar / 2 000 psi
Max. flow	40 lpm / 10 gpm (US)
Quick couplers	3/8 HTMA (ISO 16028)

BENEFITS

- Cutting from both sides of the rail in one clamping process
- Design allows precise and ergonomic cutting from a standing position
- Free floating spark guard protects user and environment
- Unbeatable power to weight ratio of hydraulic tools
- Less noise and no petrol vapours around the user
- Various power units available to power the machine

ACCESSORIES

- Replacement saw blades 356 or 406 mm / 14" or 16"
- Hose set

